

woodmax

wood adhesives



D4 WOOD
ADHESIVES

| **synthos**

woodmax

OC 14.50
TC 24.50

IFT certificate
Rosenheim



D4 CLASS ADHESIVES

The resistance to weather conditions is extremely important for wooden products for external use, such as window scantlings. For applications with special requirements Synthos offers adhesives in the D4 class of water resistance, based on an aqueous dispersion of poly(vinyl acetate). Our adhesives lead to reduced energy consumption because of lower pressing temperatures.

ONE-COMPONENT
WOODMAX® OC 14.50

TWO-COMPONENT
WOODMAX® TC 24.50

Both adhesives have the certificate issued by IFT in Rosenheim, confirming the **D4 class in accordance** with EN 204 as well as **high thermal resistance: $\geq 7 \text{ N/mm}^2$** in accordance with EN 14257 (WATT'91).

APPLICATIONS:

- window scantling
- bonding of solid wood for the production of indoor joinery installations
- indoor elements particularly prone to humidity
- bonding of softwood
- bonding of hardwood
- cold bonding
- hot bonding
- application in a high-frequency press
- finger joints

Synthos S.A.
Chemików 1
32-600 Oświęcim, POLAND
tel. +48 33 844 18 21...25

www.synthosgroup.com

For further and technical information please contact us:
woodmax.sales@synthosgroup.com